



297, Subh Estate, Nr. Jaweri Estate, Singharwa Kathwada Road, Kathwada, Ahmedabad 382330.

[Yoga24in@hotmail.com](mailto:Yoga24in@hotmail.com) | [www.globalventure.hpage.com](http://www.globalventure.hpage.com) | +91 9033817316.



### **Packaging & Delivery**

Packaging Detail: wooden case

Delivery Detail: whth in 15 days after your payment

### **Specifications**

## HT447 II offset four color offset printing machine

1)Certification of SO9001:2000

2)Easy to operation

3)Certification of CE

## HT447 II offset four color offset printing machine

Details			
Model Specification	HT47 sixto four color offset printing machine	HT56 quarto four color offset printing machine	HT62 big quarto four color offset printing machine
Max. Paper Size	470*365mm	560*400mm	620*450mm
Max. Printing Area	450*345mm	550*375mm	600*450mm
Paper Weight	28-300g/m <sup>2</sup>	28-300g/m <sup>2</sup>	28-300g/m <sup>2</sup>
Printing Speed	2000-7000sheets/h	2000-7000sheets/h	2000-7000sheets/h
Plate Size	470*395*0.15mm	560*420*0.15mm	610*480mm
Blanket Size	470*420*1.95mm	560*460*1.95mm	620*475mm
Ink Roller	16 pieces(3 pieces form ink roller	16 pieces(3 pieces form ink roller	16 pieces(3 pieces form ink roller
Power of Motor	3 Kw	3 Kw	3 Kw
Power of Air-pump Motor	0.55 Kw	0.55 Kw	0.55 Kw
Power Supply	380V/50Hz	380V/50Hz	380V/50Hz
Dimension	4300*935*1490mm	4300*1000*1490mm	4800*1100*1600mm
Net Weight	2800kg	3200kg	3800kg
Fob price	<b>91, 50, 000 INR</b>	<b>22, 50, 000 INR</b>	<b>31, 50, 000 INR</b>

1.the Rubber roller using three-point suspension technology, pneumatic clutch pressure, the pressure will be adjusted well for the accuracy and reliability, and the roller adjust will not affect each other, this protect the roller bearings properly.

2.External high-precision helical gear driver and walk-way iron cylinder to ensure a stable pressure of the printing and delivery of a smooth rotating, to ensure the large printing and very clear mesh work print or copy well, including the small text printing.

3.The whole machine use the way of self-lubricating to ensure that all gears and bearings both in the boot of lubrication at the same time when you operating it.

4.The whole unit of the ink supply Composed by 15 rollers, which including 4 different diameter rollers side by the edition, the system responds quickly, good ink absorption function, the ink duct controlled by the ink sub-control key, also can be adjusted by separately, will not affect each other, to ensure the enough ink reservoir and uniformity smoothly. The ink and water will be controlled electronically, they are all clutched pneumatically.

5.Professional high-quality and reliable feeding system ensure the paper feeding smoothly and accurately.Semi-automatic version Loading, printing version was controlled or adjusted electronically, this shorten the time of version installed and adjusted, reducing the requirements for operators.

6.The machine with the function of synchronization hydropower, when the speed of host-run version changes, then motor of lubricating also changes the speed at the same time.



**GLOBAL VENTURE IMPEX**

**Our parts 4**