



Performance

Introduce sensitization resin as flexible printing plate, suitable for printing such packing materials as polyethylene, polypropylene bag, cellophane and roll paper, etc. It is a kind of ideal printing equipment for producing paper packing bag for food, supermarket handbag, vest bag and clothes bag, etc.

Features

1. Easy operation, flexible starting, accurate color register.
2. The meter counter can set printing quantity according to the requirements. Stop the machine automatically at the quantity or when the material is cut off.

3. Pneumatic printing cylinder lift and lower, it will stir the printing ink automatically after lifting.
4. The printing ink is spread by the anilox cylinder with even ink color.
5. Reliable drying system coordinated with high-speed rotation, it will automatically break circuit when the machine stops.
6. 360° continuous and adjustable longitudinal register device.
7. The frequency control of motor speed adapts to different printing speeds.
8. There are Jogging/Stopping buttons on the plate roller base and material rolling rack so as to make it easy operate the machine when the plate is installed.
9. Magnetic powder brake for unwinding tension control, magnetic powder clutch for rewinding tension control.
10. With double unwinding &rewinding shaft

Main Technical Parameter

Type	YT-6600-12.5 Lkh	YT-6800-13.6 Lkh	AYT-61000-14.5 Lkh
Max.Effective Printing Width	560mm	760mm	960mm
Max.Web Width	600mm	800mm	1000mm
Max.Printing Speed	50m/min	50m/min	50m/min
Max.Mechanical Speed	60 m/min	60 m/min	60 m/min
Max.Diameter of Roll Material	450mm	450mm	450mm
Internal Diameter of Roll Core	76mm	76mm	76mm
Rang of Repeat Printing Length	191-914mm	191-914mm	191-914mm
Accuracy of Registration	±0.5mm	±0.5mm	±0.5mm
Plate Thickness(Bothside adhesive included)	2.38mm	2.38mm	2.38mm
Heating Power	9Kw	13.5Kw	18Kw
Total Power	15Kw	19.5Kw	24Kw
Weight of Machine	3500kg	4200kg	5000kg
Overall Dimension	L4300×W1700×H2950 mm	L4300×W1900×H2950mm	L4300×W2100×H2950mm